



BEVERAGE CATALOG



**Hose For Every Service
Since 1932**



Extremeflex Beverage Red with EZ Clean Cover

Construction: Tube: White Chlorobutyl (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03), non-phthalates compound. Cover: Wide corrugated, red, low friction material, abrasion, ozone, ageing, oil and chemical resistant, easy to clean. Reinforcement: Spiral-plyed fabrics with double galvanized helix wire.



Temperature: -30°F to 220°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	250	EXBR100	
1-1/2	250	EXBR150	
2	200	EXBR200	

Extremeflex Beverage Gray

Construction: Tube: White Chlorobutyl (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03), non-phthalates compound. Cover: Corrugated grey Nitrile Rubber/PVC compound (wrapped impression) Reinforcement: Spiral-plyed fabrics with double galvanized helix wire.



Temperature: -30°F to 220°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	250	EXBG100	
1-1/2	250	EXBG150	
2	200	EXBG200	

Novabrew

Construction: Tube: White Chlorobutyl (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03). Cover: Dark burgundy EPDM. Reinforcement: Multiple plies of polyester tire cord and dual monofilament helix rods.



Temperature: -40°F to 248°F
Sizes: 3/4" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	250	NF-6507-100	
1-1/2	250	NF-6507-150	
2		NF-6507-200	

Growler Brewery Hose

Construction: Tube: White, BIIR (BUTYL). Cover: Orange EPDM reinforced with high strength synthetic plies with steel wire spirals.



Temperature: -40°F to 248°F
Sizes: 3/4" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	150	GRLR100	
1-1/2	150	GRLR150	
2	150	GRLR200	

Connoisseurs Suction & Discharge Hose

Construction: Tube: White Chlorobutyl. Cover: Grey EPDM abrasion resistant. Reinforcement: Multiple plies of polyester tire cord & dual monofilament helix.



Temperature: -40°F to 248°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	250	NF-6506-100	
1-1/2	250	NF-6506-150	
2	250	NF-6506-200	

Connoisseurs Suction & Discharge Hose

Construction: Tube: White Chlorobutyl. Cover: Grey EPDM corrugated. Reinforcement: Multiple plies of polyester tire cord with helix wire.



Temperature: -40°F to 248°F
Sizes: 3/4" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	150	NF-6514-100	
1-1/2	150	NF-6514-150	
2	150	NF6514-200	

Fitting Options



Male Din Fitting	Female Din Fitting with nut	
1	1	
1-1/2	1-1/2	
2	2	



Crimped Tri-Clamp piece attached set	Crimped Tri-Clamps with Bumper 2 piece attached set	Crimped Tri-Clamp One Piece attached set
1	1	1
1-1/2	1-1/2	1-1/2
2	2	2

EZ Glide Wine

Construction: Tube: white chlorobutyl rubber, non-phthalates compound. Cover: Grey Nitrile Rubber/PVC compound and green outer helix reinforced with synthetic fabric plies.



Temperature: -20°F to 180°F
Sizes: 1-1/2" - 3"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	150	EXBW150	
2	150	EXBW200	

BALTHAZAR™ HD

Construction: Tube: White NBR. Cover: Gray EPDM. Reinforcement: High strength synthetic plies with steel wire spirals.



Temperature: -40°F to 248°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	150	WINE100	
1-1/2	150	WINE125	
2	150	WINE200	

Heavy-Duty Flexible PVC Hose

Construction: Clear Pliovic® PVC (FDA, 3-A, USDA compliant), NSF-61 tube. Clear Pliovic® cover. Clear high-density Pliovic® helix reinforcement.



Temperature: -15°F to 158°F
Sizes: 1 1/2" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	89	NTF150	
2	79	NTF200	

PVC Clear Standard Suction Hose

Construction: Clear PVC with white helix. Smooth wall and interior.



Temperature: -10°F to 130°F
Sizes: 1" - 2"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	90	SPT100	
1-1/2	90	SPT150	
2	70	SPT200	

WSTF Beverage Transfer Hose

Construction: Double-ply PVC tube, polyester fabric reinforcement and rigid PVC helix.



Temperature: -4°F to 150°F
Sizes: 1 1/2" - 6"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	110	WSTF150	
2	100	WSTF200	
3	100	WSTF300	
4	75	WSTF400	

Fitting Options



Male Din Fitting	Female Din Fitting with nut	
1	1	
1-1/2	1-1/2	
2	2	

Crimped Tri-Clamp piece attached set	Crimped Tri-Clamps with Bumper 2 piece attached set	Crimped Tri-Clamp One Piece attached set
2	2	1
1	1-1/2	1-1/2
2	2	2

We offer a wide variety of beverage transfer hoses to fit your individual needs. Any of these hoses can be sold in bulk or assembled with the fitting combinations below.

UHMW Tube and smooth EPDM Cover

Construction: Tube: FDA UHMW - odor and tasteless. Cover: Grey EPDM. Reinforcement: Multiple plies of polyester tire cord with helix wire.



Temperature: -40°F to 225°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	200	NF-6403-100	
1-1/2	200	NF-6403-150	
2	200	NF-6403-200	

Extra Flexible White UHMW EPDM Food

Construction: Tube: White FDA UHMW. Cover: Grey EPDM corrugated. Reinforcement: Multiple plies of polyester tire cord with helix wire. * Also available with slide cover



Temperature: -40°F to 225°F
Sizes: 1" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	250	NF-6506-100	
1-1/2	250	NF-6506-150	
2	250	NF-6506-200	

Elixir

Construction: Tube: Clear, UHMWPE. Cover: Green EPDM. Reinforcement: High strength synthetic plies with steel wire spirals.



Temperature: -4°F to 230°F
Sizes: 3/4" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	200	ELIX100	
1-1/2	200	ELIX150	
2	200	ELIX200	

WSTF Beverage Transfer Hose

Construction: Double-ply PVC tube, polyester fabric reinforcement and rigid PVC helix.



Temperature: -4°F to 150°F
Sizes: 1 1/2" - 6"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	110	WSTF150	
2	100	WSTF200	
3	100	WSTF300	
4	75	WSTF400	

Heavy-Duty Flexible PVC Hose

Construction: Clear Pliovio® PVC (FDA, 3-A, USDA compliant), NSF-61 tube. Clear Pliovio® cover. Clear high-density Pliovio® helix reinforcement.



Temperature: -15°F to 158°F
Sizes: 1 1/2" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	89	NTF150	
2	79	NTF200	

PVC Clear Standard Suction Hose

Construction: Clear PVC with white helix. Smooth wall and interior.



Temperature: -10°F to 130°F
Sizes: 1" - 2"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	90	SPT100	
1-1/2	90	SPT150	
2	70	SPT200	

Fitting Options

Choose MxM, FxF, or MxF



Male Din Fitting	Female Din Fitting with nut	
1	1	
1-1/2	1-1/2	
2	2	

Crimped Tri-Clamp piece attached set	Crimped Tri-Clamps with Bumper 2 piece attached set	Crimped Tri-Clamp One Piece attached set
1	1	1
1-1/2	1-1/2	1-1/2
2	2	2

Heavy-Duty Flexible PVC Hose

Construction: Clear Pliovic® PVC (FDA, 3-A, USDA compliant), NSF-61 tube. Clear Pliovic® cover. Clear high-density Pliovic® helix reinforcement.



Temperature: -15°F to 158°F
Sizes: 1 1/2" - 4"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	89	NTF150	
2	79	NTF200	

PVC Clear Standard Suction Hose

Construction: Clear PVC with white helix. Smooth wall and interior.



Temperature: -10°F to 130°F
Sizes: 1" - 2"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1	90	SPT100	
1-1/2	90	SPT150	
2	70	SPT200	

WSTF Beverage Transfer Hose

Construction: Double-ply PVC tube, polyester fabric reinforcement and rigid PVC helix.



Temperature: -4°F to 150°F
Sizes: 1 1/2" - 6"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose	Price per Foot
1-1/2	110	WSTF150	
2	100	WSTF200	
3	100	WSTF300	
4	75	WSTF400	

Fitting Options



Male Din Fitting	Female Din Fitting with nut	
1	1	
1-1/2	1-1/2	
2	2	

Crimped Tri-Clamp piece attached set	2	Crimped Tri-Clamps with Bumper 2 piece attached set		Crimped Tri-Clamp One Piece attached set
1		1		1
1-1/2		1-1/2		1-1/2
2		2		2

Gaskets

Size (in.)	Description	Part Number	Price/ Each
1	1" White Silicone Gasket	TC-40MP-XW100	
1-1/2	1-1/2" White Silicone Gasket	TC-40MP-XW150	
2	2" White Silicone Gasket	TC-40MP-XW200	



Clamps

Size (in.)	Description	Part Number	Price/ Each
1-1/2	1" & 1-1/2" Single Pin Clamp	TC-13MHM-150	
2	2" Single Pin Clamp	TC-13MHM-200	
1-1/2	1" & 1-1/2" Spring Clamp	TC-13MHM-Q150	
2	2" Spring Clamp	TC-13MHM-Q200	



Barbed Sanitary Adapters

Size (in.)	Description	Rubber Hose	Price/ Each	Brewery Hose	Price/ Each
1	Stainless Steel Barbed Adapters	C414MPHR-1		C414MPHRL-1	
1-1/2	Stainless Steel Barbed Adapters	C414MPHR-15		C414MPHRL-15	
2	Stainless Steel Barbed Adapters	C414MPHR-2		C414MPHRL-2	



Threaded Sanitary Adapters

Size (in.)	Description	Male NPT	Price/ Each	Female NPT	Price/ Each
1	Stainless Steel Threaded Adapters	C421MP-1		C422MP-1	
1-1/2	Stainless Steel Threaded Adapters	C421MP-15		C422MP-15	
2	Stainless Steel Threaded Adapters	C421MP-2		C422MP-2	



Butterfly Valves

FEATURES:

- Material: 316L forged stainless steel body and disc
- Seat options: silicone, EPDM, FKM
- Low resistance to flow
- Bi-directional flow
- Polyacetal bushings for the valve disc for reduced friction and increased life cycle
- All wetted surfaces are sanitary finished to $\leq 32R_x$



REPAIR KITS AVAILABLE

Size	Butterfly Valve (Viton Seat)	Price / Each	Butterfly Valve (Buna Seat)	Price / Each	Butterfly Valve (Silicone Seat)	Price / Each	Butterfly Valve (Teflon Seat)	Price / Each
1	BFV100-VITON		BFV100-BUNA		BFV100-SIL		BFV100-PTFE	
1.5	BFV150-VITON		BFV150-BUNA		BFV150-SIL		BFV150-PTFE	
2	BFV200-VITON		BFV200-BUNA		BFV200-SIL		BFV200-PTFE	
3	BFV300-VITON		BFV300-BUNA		BFV300-SIL		BFV300-PTFE	
4	BFV400-VITON		BFV400-BUNA		BFV400-SIL		BFV400-PTFE	

Sanitary Check Valves

FEATURES:

- Material: Forged 316L stainless steel
- Lower resistance to flow
- Suitable for low and medium viscosity fluids
- Full size flow plate
- Long stem bushing for better life cycle
- All wetted surfaces are sanitary finished to $\leq 32R_x$
- Operating temperature range: 15°F to 200°F
- Maximum operating pressure: 145 PSI



Size	Sanitary Spring Check Valve	Price / Each						
1	SCV100							
1.5	SCV150							
2	SCV200							
3	SCV300							
4	POR							

Rotating Sanitary Spray Balls

Application:

- ideal for cleaning all types of tanks and vessels

Features:

- stainless steel ball bearings eliminate rust
- cleaning solution lubricates unit
- mirror-like finish (OD)
- spray pattern: 360°
- available connections: clamp and NPT



Size	Spinning Spray Ball	Price / Each						
.75 NPT	SRH360NPT-G075							
1.5 CLAMP	SRH360CMP-G150							
1.5 NPT	SRH360NPT-R150							

Silicone

Construction: Raw materials meet FDA requirements per FDA 21 CFR 177.2600 for use with food contact surfaces.

Temperature: -100°F to 500°F (350°F max for NSF applications)

Sizes: 1/16" - 3/4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Tubing	Price/ Foot
3/8	10	2802086	
1/2	10	2802471	
3/4	10	2803087	



Clear PVC Tubing

Construction: Clear PVC tube

Temperature: - 10°F to 130°F

Sizes: 1/8" - 2"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Tubing	Price/ Foot
3/8	45	TPVC-0601	
1/2	30	TPVC-0801	
3/4	35	TPVC-1202	
1	25	TPVC-1602	



Reinforced PVC Tubing

Construction: Crystal clear PVC compound, formulated with ingredients in compliance with applicable FDA(03) requirements. Reinforced with spiraled polyester yarn and longitudinal orange tracer yarns for identification.

Temperature: 25°F to 150°F

Sizes: 1/4" - 2"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Tubing	Price/ Foot
1/2	200	TRPVC-08	
3/4	150	TRPVC-12	
1	125	TRPVC-16	
1-1/4	100	TRPVC-24	
1-1/2	75	TRPVC-32	



Don't see what you need? Give us a call and we can get it for you!

For pricing and availability call us at 630-607-1900

Washdown & Sanitizing Hose

Sani-Wash™ 300



Construction: EPDM synthetic rubber tube, White EPDM synthetic rubber cover with a textile reinforcement.



Temperature: -40°F to 200°F
Sizes: 1/2" - 1"

Hose Inside Dia. (in.)		Max. Pressure (psi)	Bulk Hose	Price/ Foot	Coupling Options Brass GHT, Stainless Steal/Brass GHT, Swivels, Nozzles
1/2	3/4				
1/2	3/4	300	CR050		
3/4	1	300	CR075		
1		300	CR100		



Fortress Washdown



Construction: Black nitrile synthetic rubber tube. Cover is a Yellow Carbyn™ synthetic rubber, RMA Class A (High Oil Resistance) with Microban product protection. Reinforcement is spiral synthetic yarn.



Temperature: -20°F to 200°F
Sizes: 1/2" - 1"

Hose Inside Dia. (in.)		Max. Pressure (psi)	Bulk Hose	Price/ Foot	Coupling Options Brass GHT, Stainless Steal/Brass GHT, Swivels, Nozzles
1/2	3/4				
1/2	3/4	300	FRT050		
3/4	1	300	FRT075		
1		300	FRT100		



Other Products Available Upon Request ** Stocked Locally **

Mixing Stations

Stainless Steel Gauges

Valves

Pipe Fittings

Dry Food Hoses



Sanitary Tubing

Cam & Groove Fittings

Plastic Tubing

Custom Sanitary Gaskets

Compression Fittings



Gauges

Size (in.)	Description	Part Number	Price
1-1/2"	Sanitary Stainless Steel Pressure Gauge	ESP-301LFW	
2"	Sanitary Stainless Steel Pressure Gauge	1032-200	

Tri-Clamp size, pressures and dial sizes can be customized to your needs.
Please call with specifications.



Nozzles

Size (in.)	Description	Part Number	Price
1/2"	Brass Nozzle White Cover with Swivel Adapter	SK-150B-W-A	
1/2"	SS Nozzle White Cover with Swivel Adapter	SK-150S-W-A	
1/2"	Brass Nozzle with White Cover	SK-150B-W	
1/2"	Stainless Steel Nozzle with White Cover	SK-150S-W	

Other cover colors available




Swivel Adapter

Size (in.)	Description	Part Number	Price
1/2"	1/2" Barb X 1/2" MNPT SS Swivel	SK-8-1/2-S	
1/2"	1/2" Barb X 1/2" MNPT SS Swivel Ball Type	SK-8-B1/2-S	
3/4"	3/4" Barb X 1/2" MNPT SS Swivel	SK-8-3/4-S	
3/4"	3/4" Barb X 1/2" MNPT SS Swivel Ball Type	SK-8-B3/4-S	



Mixing Units

Mixer Body	Description	Type	Part Number	Price
Brass	Mixing unit w/ globe valves	Hot & Cold	3600M-B	
Stainless	Mixing unit w/ globe valves	Hot & Cold	3600M-S	
Brass	Mixing unit w/ ball valves & temp gage	Hot & Cold	3600BM-B-T	



Hose Reel

Size (in.)	Description	Part Number	Price
3/8"	Spring retractable stainless steel hose reel w/o hose	LC607 OLS	
1/2"	Spring retractable stainless steel hose reel w/o hose	LC800 OLS	

*Hose can be added at additional cost. Contact us for details





Company Name	Telephone
Address	Fax
City, State, Zip Code	Email

When evaluating hose applications, we use the acronym "S.T.A.M.P.E.D." to be sure all the right questions are answered to you get the correct assembly for your application.

Size

Temperature

Application

Material(s) Being Conveyed

Pressure

Ends

Delivery

Additional Information