



CATALOG


Serving Construction and Industrial Supply Since 1932



Industrial Hose



Couplings & Accessories



Beverage Hose



Tubing



Hydraulic Hose & Fittings





Company Name	Telephone
Address	Fax
City, State, Zip Code	Email

When evaluating hose applications, we use the acronym "S.T.A.M.P.E.D." to be sure all the right questions are answered to you get the correct assembly for your application.

Size

Temperature

Application

Material(s) Being Conveyed

Pressure

Ends

Delivery

Additional Information

Suction Hose Couplings

Aluminum with Brass Swivel Nut

Size (in.)	Complete Set	Price/ Set	Female Only	Price/ Each	Male Only	Price/ Each
1-1/2	MF150		MF150-F		MF150-M	
1-1/2 NST	MF150-NST		MF150-NST-F		MF150-NST-M	
2	MF200		MF200-F		MF200-M	
2-1/2	MF250		MF250-F		MF250-M	
2-1/2 NST	MF250-NST		MF250-NST-F		MF250-NST-M	
3	MF300		MF300-F		MF300-M	
4	MF400		MF400-F		MF400-M	
6	MF600		MF600-F		MF600-M	

* NSPM thread except where indicated



Spanner Wrenches

For Pin Lug Suction Couplings

Size (in.)	Part Number	Price/ Each
1-1/2	SW150	
2	SW200	
2-1/2	SW250	
3	SW300	
4	SW400	
6	SW600	
1½ x 2½"	SW150-250	



Rubber Washers

For Suction Hose Couplings

Size (in.)	Part Number	Price/ Each
1-1/2	GASK-150	
1-1/2 NST	GASK-150-NST	
2	GASK-200	
2-1/2	GASK-250	
2-1/2 NST	GASK-250-NST	
3	GASK-300	
4	GASK-400	
6	GASK-600	



Steel Strainers

Round or Square Hole

Size (in.)	Type	Part Number	Price/ Each
1-1/2	Round Hole	STR-RH150	
1-1/2	Square Hole	STR-SH150	
2	Round Hole	STR-RH200	
2	Square Hole	STR-SH200	
2-1/2	Round Hole	STR-RH250	
2-1/2	Square Hole	STR-SH250	
3	Round Hole	STR-RH300	
3	Square Hole	STR-SH300	
4	Round Hole	STR-RH400	
4	Square Hole	STR-SH400	
6	Round Hole	STR-RH600	
6	Square Hole	STR-SH600	



Adjustable Lexan Hose Nozzle

Size (in.)	Lexan	Price/ Each
3/4 GHT	NOZZ-FOG75-GHT	
1 IPT	NOZZ-FOG100	
1-1/2 IPT or NST	NOZZ-FOG150	
2 IPT	NOZZ-FOG200	



Adjustable Brass Hose Nozzle

Size (in.)	Brass	Price/ Each
3/4 GHT	NOZZ-FOG75-BR	
1 IPT	NOZZ-FOG100-BR	
1-1/2 IPT or NST	NOZZ-FOG150-BR	
2 IPT	NOZZ-FOG200-BR	



Steel Hose Menders

Size (in.)	Type	Price/ Each
1/2	MEND-050-ST	
5/8	MEND-058-ST	
3/4	MEND-075-ST	
1	MEND-100-ST	
1-1/4	MEND-125-ST	
1-1/2	MEND-150-ST	
2	MEND-200-ST	
3	MEND-300-ST	
4	MEND-400-ST	



Brass Hydrant Adapters

Size (in.)	Type	Price/ Each
2-1/2 FNST X GHT	DX-HA2576	
2-1/2 FNST X 1 MIPT	DX-HA2510T	
2-1/2 FNST X 1 1/2 MIPT	DX-HA2515T	
2-1/2 FNST X 2 MIPT	DX-HA2520T	
2-1/2 FNST X 3 MIPT	DX-HA2530T	
4-1/2 FNST X 2-1/2 MNST	DX-HA4525F	



Adjustable Hydrant Wrench

Size (in.)	Type	Price/ Each
NA	HYD-1	



Cam & Groove Quick Couplings

Aluminum



Hose Size (in.)	Part A Female Adapter	Price/ Each	Part B Male Coupler	Price/ Each	Part C Hose Shank Coupler	Price/ Each	Part D Female Coupler	Price/ Each	Part E Hose Shank Adapter	Price/ Each
1	QC-A100		QC-B100		QC-C100		QC-D100		QC-E100	
1-1/2	QC-A150		QC-B150		QC-C150		QC-D150		QC-E150	
2	QC-A200		QC-B200		QC-C200		QC-D200		QC-E200	
3	QC-A300		QC-B300		QC-C300		QC-D300		QC-E300	
4	QC-A400		QC-B400		QC-C400		QC-D400		QC-E400	
6	QC-A600		QC-B600		QC-C600		QC-D600		QC-E600	



Hose Size (in.)	Part F Male Adapter	Price/ Each	Part DC Dust Cap	Price/ Each	Part DP Dust Plug	Price/ Each	Quick Coupler Gasket	Price/ Each	Cone Strainer (for use with Part C)	Price/ Each
1	QC-F100		QC-DC100		QC-DP100		GASK-QC100			
1-1/2	QC-F150		QC-DC150		QC-DP150		GASK-QC150			
2	QC-F200		QC-DC200		QC-DP200		GASK-QC200			
3	QC-F300		QC-DC300		QC-DP300		GASK-QC300			
4	QC-F400		QC-DC400		QC-DP400		GASK-QC400			
6	QC-F600		QC-DC600		QC-DP600		GASK-QC600			

Polypropylene

Hose Size (in.)	Part A Female Adapter	Price/ Each	Part B Male Coupler	Price/ Each	Part C Hose Shank Coupler	Price/ Each	Part D Female Coupler	Price/ Each	Part E Hose Shank Adapter	Price/ Each
1	QC-A100-PP		QC-B100-PP		QC-C100-PP		QC-D100-PP		QC-E100-PP	
1-1/2	QC-A150-PP		QC-B150-PP		QC-C150-PP		QC-D150-PP		QC-E150-PP	
2	QC-A200-PP		QC-B200-PP		QC-C200-PP		QC-D200-PP		QC-E200-PP	
3	QC-A300-PP		QC-B300-PP		QC-C300-PP		QC-D300-PP		QC-E300-PP	
4	QC-A400-PP		QC-B400-PP		QC-C400-PP		QC-D400-PP		QC-E400-PP	

Hose Size (in.)	Part F Male Adapter	Price/ Each	Part DC Dust Cap	Price/ Each	Part DP Dust Plug	Price/ Each	Quick Coupler Gasket	Price/ Each	Cone Strainer (for use with Part C)	Price/ Each
1	QC-F100-PP		QC-DC100-PP		QC-DP100-PP		GASK-QC100			
1-1/2	QC-F150-PP		QC-DC150-PP		QC-DP150-PP		GASK-QC150			
2	QC-F200-PP		QC-DC200-PP		QC-DP200-PP		GASK-QC200			
3	QC-F300-PP		QC-DC300-PP		QC-DP300-PP		GASK-QC300			
4	QC-F400-PP		QC-DC400-PP		QC-DP400-PP		GASK-QC400			

Stainless Steel

Hose Size (in.)	Part A Female Adapter	Price/ Each	Part B Male Coupler	Price/ Each	Part C Hose Shank Coupler	Price/ Each	Part D Female Coupler	Price/ Each	Part E Hose Shank Adapter	Price/ Each
1	QC-A100-SS		QC-B100-SS		QC-C100-SS		QC-D100-SS		QC-E100-SS	
1-1/2	QC-A150-SS		QC-B150-SS		QC-C150-SS		QC-D150-SS		QC-E150-SS	
2	QC-A200-SS		QC-B200-SS		QC-C200-SS		QC-D200-SS		QC-E200-SS	
3	QC-A300-SS		QC-B300-SS		QC-C300-SS		QC-D300-SS		QC-E300-SS	
4	QC-A400-SS		QC-B400-SS		QC-C400-SS		QC-D400-SS		QC-E400-SS	
6	QC-A600-SS		QC-B600-SS		QC-C600-SS		QC-D600-SS		QC-E600-SS	

Hose Size (in.)	Part F Male Adapter	Price/ Each	Part DC Dust Cap	Price/ Each	Part DP Dust Plug	Price/ Each	Quick Coupler Gasket	Price/ Each	Cone Strainer (for use with Part C)	Price/ Each
1	QC-F100-SS		QC-DC100-SS		QC-DP100-SS		GASK-QC100			
1-1/2	QC-F150-SS		QC-DC150-SS		QC-DP150-SS		GASK-QC150			
2	QC-F200-SS		QC-DC200-SS		QC-DP200-SS		GASK-QC200			
3	QC-F300-SS		QC-DC300-SS		QC-DP300-SS		GASK-QC300			
4	QC-F400-SS		QC-DC400-SS		QC-DP400-SS		GASK-QC400			
6	QC-F600-SS		QC-DC600-SS		QC-DP600-SS		GASK-QC600			

Eliminate spills due to cam lock arms opening up accidentally. Safety Locks are an alternative to Velcro straps. Easy to install and easy to remove, Safety Locks click into place over the cam lock arms.

Food Grade Safety Bump

Size (in.)	Description	Part Number	Price/ Each
2	Food Grade Female	SBF-2F	
2	Food Grade Male	SBM-2F	
3	Food Grade Female	SBF-3F	
3	Food Grade Male	SBM-3F	
4	Food Grade Female	SBF-4F	
4	Food Grade Male	SBM-4F	



Anti-Static Safety Bump

Size (in.)	Description	Brass	Price/ Each
2	Anti-Static Female	SBF-2P	
2	Anti-Static Male	SBM-2P	
3	Anti-Static Female	SBF-3P	
3	Anti-Static Male	SBM-3P	
4	Anti-Static Female	SBF-4P	
4	Anti-Static Male	SBM-4P	



Septic Safety Bump

Size (in.)	Description	Type	Price/ Each
2	Septic Female	SBF-2S	
2	Septic Male	SBM-2S	
3	Septic Female	SBF-3S	
3	Septic Male	SBM-3S	
4	Septic Female	SBF-4S	
4	Septic Male	SBM-4S	



Safety Locks

Size (in.)	Description	Type	Price/ Each
2	Blue	SL-2	
3	Red	SL-3	
4	Orange	SL-4	



4½" NST Brass Hydrant Adapters

Size (in.)	Description	Part Number	Price/ Each
1-1/2	Male NPT Outlet	HYD-4515T	
2	Male NPT Outlet	HYD-4520T	
2-1/2	Male NST Outlet	HYD-4525F	
3	Male NPT Outlet	HYD-4530T	
3/4	GHT Outlet	HYD-4576	



Fire Hose Accessories

Size (in.)	Description	Part Number	Price/ Each
	Heavy Duty Adjustable Hydrant Wrench	HYD-1	
2	2½" Female swivel NST x 2½" Male NST Aluminum Hydrant Gate Valve	HGV25	
3	2½" Female swivel NST x 2½" Male NST Brass Hydrant Gate Valve	HGV25-B	
3	2½" Female NST Swivel Inlet x (2) 1½" Male NST Outlets	WV2515	



Hose Rack & Reel Covers

Size (in.)	Description	Part Number	Price/ Each
28	Fits 50' and 75' pin type hose racks	RA28	
32	Fits 100' and 125' pin type hose racks	RA32	
18	Fits 16" and 18" hose reels	RE18	
24	Fits 24" hose reels	RE24	



Fire Hose Swing Wall Reel

Hose is easily removed by pulling toward fire area. Instantly ready for action when completely removed, and valve is opened.

Construction: Heavy duty construction. One piece wall bracket for easy mounting- 180 swing will also take pipe clamps to 3". Baked red enamel finish.

Size (in.)	Dimensions	Part Number	Price/ Each
1-1/2	18" x 23.5" x 6.25"	R 15-18	
1-1/2	24" x 29" x 6.25"	R 15-24	
2-1/2	24" x 29" x 8.25"	R 25-24	



Single Jacket Fire Hose

Construction: 100% polyester jacket with a high grade single ply extruded EPDM rubber lining

Aluminum M + F NST					
Hose Inside Dia. (in.)	Max. Pressure (psi)	50 ft Assy M + F NST	Price	100 ft Assy M + F NST	Price
1½	300	SF315-050-ARN		SF315-100-ARN	
2½	300	SF325-050-ARN		SF325-100-ARN	

Brass M + F NST					
Hose Inside Dia. (in.)	Max. Pressure (psi)	50 ft Assy M + F NST	Price	100 ft Assy M + F NST	Price
1½	300	SF315-050-BRN		SF315-100-BRN	
2½	300	SF325-050-BRN		SF325-100-BRN	



Double Jacket Hose

Construction: 100% polyester double jacket construction with a high grade single ply extruded EPDM rubber lining.

Aluminum M + F NST					
Hose Inside Dia. (in.)	Max. Pressure (psi)	50 ft Assy M + F NST	Price	100 ft Assy M + F NST	Price
1½	800	DF815-050-ARN		DF815-100-ARN	
1-3/4	800	DF817-050-ARN		DF817-100-ARN	
2½	800	DF825-050-ARN		DF825-100-ARN	



Pin Rack Hose

Construction: Pre-folded pin rack fire hose

Aluminum M + F NST							
Hose Inside Dia. (in.)	Max. Pressure (psi)	50 ft Assy M + F NST	Price	75 ft Assy M + F NST	Price	100 ft Assy M + F NST	Price
1½	250	RR15-050-ARN		RR15-075-ARN		RR15-100-ARN	
2½	250	RR25-050-ARN					

Brass M + F NST							
Hose Inside Dia. (in.)	Max. Pressure (psi)	50 ft Assy M + F NST	Price	75 ft Assy M + F NST	Price	100 ft Assy M + F NST	Price
1½	250	RR15-050-BRNU		RR15-075-BRNU		RR15-100-BRNU	
2½	250	RR25-050-BRNU					





PVC Blue

Standard-duty water discharge in construction, agricultural, and marine service.

Size: 1-1/2" to 4"

Temperature: -10°F to 150°F

Pressure: 35 psi to 90 psi



PVC Red

Medium-duty discharge in mining, construction, industry, agriculture, and marine service. Limited oil and chemical application.

Size: 1-1/2" to 4"

Temperature: -10°F to 150°F

Pressure: 100 psi to 150 psi



PVC/Nitrile Yellow

Heavy-duty discharge in mining, agriculture, construction and marine service. Limited oil and chemical application. Stands up well to abrasion.

Size: 1-1/2" to 4"

Temperature: -10°F to 150°F

Pressure: 150 psi to 200 psi



Rubber

Medium-duty rubber discharge for service in quarries, mines, construction, and abrasive environments.

Size: 1-1/2" to 4"

Temperature: -25°F to 180°F

Pressure: 125 psi



High-Pressure Nitrile/PVC- Layflat

Heavy-duty, high pressure water discharge in abrasive environments. Limited oil and chemical application.

Size: 1-1/2" to 6"

Temperature: -35°F to 170°F

Pressure: 250 psi



For pumping water uphill and around tight bends, use non-collapsible water suction & discharge hose.

LAYFLAT WATER DISCHARGE HOSE

Layflat PVC and Rubber Discharge Hoses are designed for open end water discharge service. Strong, lightweight, and a great choice for pumping applications in construction, mining, agricultural, and water removal. Layflat hose coils up flat for easy storage and transport.

Layflat Water Discharge Hose

PVC Blue (Standard Duty)

Construction: Blue PVC compound tube and cover. Synthetic fabric reinforcement.

Temperature: -10°F to 150°F

Sizes: Available up to 16"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	50 ft Assy C + E	Price
1½	90	DP150-25MF		DP150-50MF		DP150-50CE	
2	80	DP200-25MF		DP200-50MF		DP200-50CE	
3	55	DP300-25MF		DP300-50MF		DP300-50CE	
4	50	DP400-25MF		DP400-50MF		DP400-50CE	
6	35	DP600-25MF		DP600-50MF		DP600-50CE	

PVC Red (Heavy Duty)

Construction: Black PVC/ Nitrile Rubber tube. Red PVC, MSHA 2G-14C/16 cover. Spiral synthetic yarn, one layer longitudinal synthetic yarn reinforcement.

Temperature: -10°F to 150°F

Sizes: Available up to 8"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	50 ft Assy C + E	Price
1½	150	DPH150-25MF		DPH150-50MF		DPH150-50CE	
2	150	DPH200-25MF		DPH200-50MF		DPH200-50CE	
3	125	DPH300-25MF		DPH300-50MF		DPH300-50CE	
4	100	DPH400-25MF		DPH400-50MF		DPH400-50CE	
6	100	DPH600-25MF		DPH600-50MF		DPH600-50CE	

Single Jacket Mill Hose

Construction:

Temperature: -10°F to 150°F

Sizes: Available up to 6"

Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	50 ft Assy C + E	Price
1½	125	DM150-25MF		DM150-50MF		DM150-50CE	
2	125	DM200-25MF		DM200-50MF		DM200-50CE	
3	125	DM300-25MF		DM300-50MF		DM300-50CE	
4	125	DM400-25MF		DM400-50MF		DM400-50CE	

PVC/Nitrile Yellow (Heavy Duty)

Construction: Black PVC/ Nitrile Rubber tube. Yellow fire-retardant PVC, MSHA 2G-14C/15 cover. Synthetic fabric reinforcement.

Temperature: -10°F to 150°F

Sizes: Available up to 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	50 ft Assy C + E	Price
1½	200	DPY150-25MF		DPY150-50MF		DPY150-50CE	
2	200	DPY200-25MF		DPY200-50MF		DPY200-50CE	
3	200	DPY300-25MF		DPY300-50MF		DPY300-50CE	
4	150	DPY400-25MF		DPY400-50MF		DPY400-50CE	



Layflat Water Discharge Hose

Rubber

Construction: Black EPDM synthetic rubber tube, Black EPDM (wrapped finish) cover, and spiral-plied synthetic fabric reinforcement.

Temperature: -10°F to 150°F

Sizes: Available up to 16"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	25 ft Assy C + E	Price
1½	125	RD150-25MF		RD150-50MF		RD150-25CE	
2	125	RD200-25MF		RD200-50MF		RD200-25CE	
3	125	RD300-25MF		RD300-50MF		RD300-25CE	
4	125	RD400-25MF		RD400-50MF		RD400-25CE	
6	125	RD600-25MF		RD600-50MF		RD600-25CE	

High- Pressure Nitrile/PVC

Construction: Yellow PVC/ Nitrile tube and cover. High tenacity polyester yarn reinforcement.

Temperature: -35°F to 170°F

Sizes: Available up to 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel				Alum. Cam and Groove	
		25 ft Assy M + F	Price	50 ft Assy M + F	Price	50 ft Assy C + E	Price
1½	250	RC150-25MF		RC150-50MF		RC150-25CE	
2	250	RC200-25MF		RC200-50MF		RC200-25CE	
3	250	RC300-25MF		RC300-50MF		RC300-25CE	
4	250	RC400-25MF		RC400-50MF		RC400-25CE	
6	250	RC600-25MF		RC600-50MF		RC600-25CE	

Suction/Discharge Pump Kits

Includes: 20ft green PVC suction hose, suction hose strainer, 50ft blue PVC lay-flat discharge hose, and gaskets.



Hose Inside Dia. (in.)	Connect Size (in.)	Pump Hose Kit		Quick Coupling Pump Hose Kit	
1½	1½	PKM1-150		PKQ1-150	
2	2	PKM1-200		PKQ1-200	
3	3	PKM1-300		PKQ1-300	
4	4	PKM1-400		PKQ1-400	



SUCTION & DISCHARGE HOSE

150 Black Synthetic Rubber

EPDM rubber general purpose hose for medium to heavy-duty operations.

Size: 1" to 14"
Temperature: -25°F to 200°F
Pressure: 150 psi
Vacuum Rating: 29 In/Hg



Clear/White PVC

General purpose PVC water suction and discharge hose for industrial, agricultural, construction and septic tank cleaning applications. Corrugated construction provides a flexible and lightweight hose for ease of handling.

Size: 1" to 4"
Temperature: 0°F to 158°F
Pressure: 35 psi to 60 psi
Vacuum Rating: 29 In/Hg



Low Temp PVC Suction Hose

A lightweight medium-duty water suction and discharge hose for industrial, construction, agricultural, mining and other applications where low temperature flexibility is required.

Size: 3/4" to 6"
Temperature: -40°F to 150°F
Pressure: 47 psi to 120 psi
Vacuum Rating: 29 In/Hg



1600 Green PVC

For water suction and discharge service in construction and septic tank cleaning operations, and for general industrial and agricultural applications where mild chemical resistance is required.

Size: 3/4" to 10"
Temperature: 0°F to 158°F
Pressure: 35 psi to 130 psi
Vacuum Rating: 29 In/Hg



Green Hornet™ All Weather EPDM/ Polyethylene

Medium-duty, light-weight construction; retains flexibility in cold weather. Smooth-bore tube minimizes material buildup and resists a variety of chemicals found in agricultural and sanitary industries. Slightly corrugated outer helix promotes abrasion resistance, low coefficient of friction and ease of coupling. Common uses can be found in waste management, construction, agricultural, marine and manufacturing industries.

Size: 1-1/4" to 6"
Temperature: -40°F to 180°F
Pressure: 25 psi to 50 psi
Vacuum Rating: 29 In/Hg



Tigertail® Crushproof Suction Hose

Double helix design allows for superior flexibility and durability. Ideal for waste evacuation, septic pumping & sewer cleaning. Superior abrasion, better crush resistance & resists kinking.

Size: 1-1/2" to 4"
Temperature: -40°F to 140°F
Pressure: 7 psi to 26 psi
Vacuum Rating: 29 In/Hg



Suction & Discharge Hoses are designed with an internal helix reinforcement in the hose wall to prevent collapsing. They are used in suction, gravity flow, and pressure service in construction, mining, agriculture, and industrial applications.



Suction & Discharge Hose

150 Black Synthetic Rubber

Construction: Black EPDM rubber tube. Black EPDM rubber (wrapped finish) cover. Synthetic fabric plies with internal wire helix reinforcement.

Temperature: -25°F to 200°F

Sizes: 1 1/2" - 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel		Alum. (F) Camlock + Steel (M) NPT		Alum. Cam and Groove	
		20 ft Assy M + F	Price	20 ft Assy C + N	Price	20 ft Assy C + E	Price
1½	150	RSG150-20MF		RSG150-20CN		RSG150-20CE	
2	150	RSG200-20MF		RSG200-20CN		RSG200-20CE	
3	150	RSG300-20MF		RSG300-20CN		RSG300-20CE	
4	150	RSG400-20MF		RSG400-20CN		RSG400-20CE	
6	150	RSG600-20MF		RSG600-20CN		RSG600-20CE	

Clear/White PVC

Construction: Clear Plivoc tube. High-density white rigid Plivoc helix reinforcement.

Temperature: 0°F to 158°F

Sizes: 3/4" - 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel		Alum. (F) Camlock + Steel (M) NPT		Alum. Cam and Groove	
		20 ft Assy M + F	Price	20 ft Assy C + N	Price	20 ft Assy C + E	Price
1	60	SPC100-20MF				SPC100-20CE	
1.25	50	SPC125-20MF				SPC125-20CE	
1½	50	SPC150-20MF				SPC150-20CE	
2	40	SPC200-20MF				SPC200-20CE	
3	35	SPC300-20MF				SPC300-20CE	
4	35	SPC400-20MF				SPC400-20CE	

1600 Green PVC

Construction: Olive green Plivoc™ tube. High-density white rigid Plivoc helix reinforcement.

Temperature: 0°F to 158°F

Sizes: 1 1/2" - 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel		Alum. (F) Camlock + Steel (M) NPT		Alum. Cam and Groove	
		20 ft Assy M + F	Price	20 ft Assy C + N	Price	20 ft Assy C + E	Price
1½	89	SP150-20MF				SP150-20CE	
2	79	SP200-20MF				SP200-20CE	
3	65	SP300-20MF				SP300-20CE	
4	55	SP400-20MF				SP400-20CE	
6	47	SP600-20MF				SP600-20CE	

Low Temp PVC Suction Hose

Construction: Clear flexible PVC tube. Blue rigid PVC helix reinforcement.

Temperature: -40°F to 150°F

Sizes: 1 1/2" - 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel		Alum. Cam and Groove	
		20 ft Assy M + F	Price	20 ft Assy C + E	Price
1½	89	CBS150-20MF		CBS150-20CE	
2	80	CBS200-20MF		CBS200-20CE	
3	65	CBS300-20MF		CBS300-20CE	
4	55	CBS400-20MF		CBS400-20CE	

Green Hornet™ All Weather EPDM/ Polyethylene

Construction: Black thermoplastic rubber, RMA Class B (medium oil resistance) tube. Rigid, lime-green polyethylene helix reinforcement; available in a variety of custom colors

Temperature: -40°F to 180°F

Sizes: 1 1/2" - 6"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F w/brass swivel		Alum. (F) Camlock + Steel (M) NPT		Alum. Cam and Groove		Hose Length (ft)
		20 ft Assy M + F	Price	20 ft Assy MNPT + F	Price	20 ft Assy C + E	Price	
1½	50	GH150-20MF				GH150-20CE		20
1½	50	GH150-25MF				GH150-25CE		25
2	50	GH200-20MF				GH200-20CE		20
2	50	GH200-25MF				GH200-25CE		25
3	45	GH300-20MF				GH300-20CE		20
3	45	GH300-25MF				GH300-25CE		25
4	40	GH400-20MF				GH400-20CE		20
6	25	GH600-20MF				GH600-20CE		20

Tigertail® Crushproof Suction Hose

Construction: Rugged polyethylene copolymer hose reinforced with an integral polyethylene helix

Temperature: -40°F to 140°F

Sizes: 1 1/2" - 3"



Hose Inside Dia. (in.)	Max. Pressure (psi)	No Fittings		Alum. M + F w/brass swivel		Alum. (F) Camlock + Steel (M) NPT	
		20 ft Bulk Hose	Price	20 ft Assy M + F	Price	20 ft Assy MNPT + F	Price
1½	26	SH150-20		SH150-20MF			
2	17	SH200-20		SH200-20MF			
3	12	SH300-20		SH300-20MF			
4		SH400-20		SH400-20MF			



Chem One™

For the transfer of a variety of current industrial chemicals used today. (Refer to Goodyear Engineered Products Chemical Resistance Guide for compatibility.) For use in pressure, gravity flow and/or suction service. Hose may be cleaned using open-end steam up to 50 psi or in a bath containing 10% Sodium Hydroxide (NaOH), up to 212°F (100°C).

▪ Size: 3/4" to 4" ▪ Temperature: -40°F to 250°F ▪ Pressure: 200 psi



Hi-Per®

A premium hose which is FEP (Fluorinated Ethylene-Propylene) lined to handle a broad spectrum of fluids and materials in a wide variety of applications

▪ Size: 1/2" to 3" ▪ Temperature: -40°F to 300°F ▪ Pressure: 200 psi



Plicord® Flexwing®

For use in tank truck and in-plant operations to transfer gasoline, oil, ethanol blends and other petroleum base products up to 50% aromatic content. It is designed for pressure, gravity flow, or full-suction service -

▪ Size: 3/4" to 8" ▪ Temperature: -35°F to 200°F ▪ Pressure: 150 psi



Plicord® ExtremeFlex®

A high-tech, flexible and versatile chemical hose capable of handling a wide range of chemicals, acids and alcohols in both suction and discharge service.

▪ Size: 1/2" to 4" ▪ Temperature: -40°F to 221°F ▪ Pressure: 150 psi



Flexwing VersaFuel™

For use in tank truck and in-plant operation to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content.

▪ Size: 1" to 4" ▪ Temperature: -30°F to 180°F ▪ Pressure: 150 psi



Chemical & Petroleum Transport Hose

Chemical transfer hoses can be found in a wide variety of process industries. Our offerings handle 95%-98% of all common chemicals. Petroleum transfer hoses are used in tank truck and in-plant applications for loading and unloading petroleum products. Both chemical and petroleum hoses are often found in applications requiring custom lengths or couple combinations.

Chem One™

Construction: Black corrugated abrasion-resistant Omegasyn™, Spiral-plied synthetic fabric with double wire helix

Temperature: -40°F to 250°F

Sizes: Available up to 4"



			Stainless Steel Cam & Groove			
Hose Inside Dia. (in.)	Max. Pressure (psi)	Bend Radius (in)	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1	200	3	CHX100-10CE		CHX100-20CE	
1½	200	4	CHX150-10CE		CHX150-20CE	
2	200	5	CHX200-10CE		CHX200-20CE	
2½	200	6	CHX250-10CE		CHX250-20CE	
3	200	8	CHX300-10CE		CHX300-20CE	

Hi-Per®

Construction: Blue Versigard® synthetic rubber with bright orange spiral transfer tape (wrapped impression), Spiral-plied synthetic fabric with double wire helix

Temperature: -40°F to 300°F

Sizes: Available up to 3"



			Stainless Steel Cam & Groove			
Hose Inside Dia. (in.)	Max. Pressure (psi)	Bend Radius (in)	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1/2	200	3	CHT050-10CE		CHT050-20CE	
3/4	200	5	CHT075-10CE		CHT075-20CE	
1	200	8	CHT100-10CE		CHT100-20CE	
1-1/2	200	14	CHT150-10CE		CHT150-20CE	

Flexwing VersaFuel™

Construction: Synthetic rubber tube. Cover is black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion. Reinforced with spiral plied synthetic fabric with helix wire.

Temperature: -30°F to 180°F

Sizes: Available up to 4"



			Brass M + F	
Hose Inside Dia. (in.)	Max. Pressure (psi)	Bend Radius (in)	25 ft Assy C + E	Price
1	150	2		
1-1/2	150	4		
2	150	5		
3	150	7		

Plicord® ExtremeFlex®

Construction: Corrugated Purple Versigard® (EPDM) synthetic rubber with yellow spiral stripe, Spiral-plied synthetic fabric with double wire helix

Temperature: -40°F to 221°F

Sizes: Available up to 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Brass M + F				Alum Cam and Groove			
		25 ft Assy	Price	50 ft Assy	Price	25 ft Assy	Price	50 ft Assy	Price
1	250	PTX100-25MF		PTX100-50MF		PTX100-25CE		PTX100-50CE	
1½	250	PTX150-25MF		PTX150-50MF		PTX150-25CE		PTX150-50CE	
2	250	PTX200-25MF		PTX200-50MF		PTX200-25CE		PTX200-50CE	
3	250	PTX300-25MF		PTX300-50MF		PTX300-25CE		PTX300-50CE	

Plicord® Flexwing®

Construction: Black (red spiral stripe) or Red Chemivic™ (white spiral stripe) synthetic rubber (oil resistant); smooth cover; wrapped finish, Spiral-plied synthetic fabric with wire helix

Temperature: -35°F to 200°F

Sizes: Available up to 8"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Brass M + F				Alum Cam and Groove			
		25 ft Assy	Price	50 ft Assy	Price	25 ft Assy	Price	50 ft Assy	Price
¾	150	PTH075-25MF		PTH075-50MF		PTH075-25CE		PTH075-50CE	
1	150	PTH100-25MF		PTH100-50MF		PTH100-25CE		PTH100-50CE	
1½	150	PTH150-25MF		PTH150-50MF		PTH150-25CE		PTH150-50CE	
2	150	PTH200-25MF		PTH200-50MF		PTH200-25CE		PTH200-50CE	
3	150	PTH300-25MF		PTH300-50MF		PTH300-25CE		PTH300-50CE	



Food & Beverage Hose

Food & Beverage Hoses come in many styles due to the wide variety of requirements in food processing: dry foods, liquid slurries; oily, non-oily, and applications requiring agency approvals. Many food

Nutriflex® Lightweight PVC with Static Wire

For handling almost every type of dry bulk food material or liquid in gravity flow and vacuum service. Nutriflex Static Wire conforms to USDA Meat and Poultry, 3-A Sanitary, and FDA Standards and is recommended for transmission of powder pellets or granular materials.

▪ Size: 1-1/2" to 6" ▪ Temperature: -15°F to 158°F ▪ Pressure: 35 psi to 50 psi



Nutriflo® Heavy-Duty PVC Hose

For handling almost every type of dry bulk food material or liquid in gravity flow and vacuum service. Nutriflo conforms to USDA Meat and Poultry, 3-A Sanitary, and FDA Standards and is used for the transmission of raw and pasteurized milk and other high water content dairy items.

▪ Size: 3/4" to 4" ▪ Temperature: -15°F to 158°F ▪ Pressure: 55 psi to 106 psi



White Flexwing® Heavy-Duty Rubber Hose

A highly flexible hose for gravity flow, pressure, or suction service transferring oily and non-oily edibles from tank truck and in-plant service.

▪ Size: 3/4" to 5" ▪ Temperature: -25°F to 230°F ▪ Pressure: 150 psi



Vitner™ Beverage Hose

For handling in-plant and/or tank truck transfer of wine, beer, potable water, and other non-oily, liquid foodstuffs.

▪ Size: 1" to 3" ▪ Temperature: -30°F to 220°F ▪ Pressure: 250 psi



Harvest™ Dry Food Hose

For tank truck and/or in-plant applications for the transfer of dry, non-oily bulk foodstuffs.

▪ Size: 2" to 5" ▪ Temperature: -25°F to 180°F ▪ Pressure: 150 psi



Plicord® Blue Flour Discharge Hose

Tank truck or in-plant service hose is for discharge transfer of abrasive materials and dry foods such as flour, cake mixes, etc.

▪ Size: 2" to 5" ▪ Temperature: -40°F to 180°F ▪ Pressure: 150 psi



Plicord® Brewline® Brewers Hose

A quality discharge hose designed specifically for the highly demanding service of transferring non-oily liquid products in wineries and breweries.

▪ Size: 3/4" to 4" ▪ Temperature: -40°F to 220°F ▪ Pressure: 250 psi



Plicord® ExtremeFlex™ Food Grade Wet Food Hose

A high-tech, flexible corrugated hose with pretzel-like agility and proven performance.

▪ Size: 2" to 4" ▪ Temperature: -25°F to 212°F ▪ Pressure: 150 psi



Harvest™ Dry Food Hose

Construction: FDA, White Pureten™ (natural rubber) (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03) tube. Gray Versigard® synthetic rubber (corrugated)/orange branding tape(wrapped impression) cover. Spiral-ply synthetic fabric with double galvanized wire helix reinforcement.

Temperature: -25°F to 180°F

Sizes: 2" - 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Alum. Cam and Groove			
		50 ft	Price	100 ft	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
2	150	HAR200-50		HAR200-100		HAR200-10CE		HAR200-20CE	
3	150	HAR300-50		HAR300-100		HAR300-10CE		HAR300-20CE	
4	150	HAR400-50		HAR400-100		HAR400-10CE		HAR400-20CE	

Nutriflo® Heavy-Duty PVC Hose

Construction: Clear Pliovic® (FDA, 3-A, USDA compliant), NSF-61 tube. Clear Pliovic cover. White or Clear high-density Pliovic® helix reinforcement.

Temperature: -15°F to 158°F

Sizes: 1 1/2" - 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Alum. M + F NPSM				Alum. Cam and Groove			
		10 ft Assy M + F (NPSM)	Price	20 ft Assy M + F (NPSM)	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1½	89	NTF150-10MF		NTF150-20MF		NTF150-10CE		NTF150-20CE	
2	79	NTF200-10MF		NTF200-20MF		NTF200-10CE		NTF200-20CE	
3	65	NTF300-10MF		NTF300-20MF		NTF300-10CE		NTF300-20CE	
4	55	NTF400-10MF		NTF400-20MF		NTF400-10CE		NTF400-20CE	

Vitner™ Beverage Hose

Construction: White Chlorobutyl (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03) tube. Gray Versigard® synthetic rubber (wrapped)/purple branding tape cover. Spiral-ply synthetic fabric with Monofilament Helix reinforcement.

Temperature: -30°F to 220°F

Sizes: 1" - 3"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Tri-Clamp				Alum. Cam and Groove			
		10 ft Assy	Price	20 ft Assy	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1	250	VNT100-10		VNT100-20		VNT100-10CE		VNT100-20CE	
1-1/2	250	VNT150-10		VNT150-20		VNT150-10CE		VNT150-20CE	
2	250	VNT200-10		VNT200-20		VNT200-10CE		VNT200-20CE	
2-1/2	250	VNT250-10		VNT250-20		VNT250-10CE		VNT250-20CE	
3	250	VNT300-10		VNT300-20		VNT300-10CE		VNT300-20CE	

Nutriflex® Lightweight PVC with Static Wire

Construction: Clear Pliovic® (FDA, 3-A, USDA compliant), NSF-61 tube. Cover is clear Pliovic (corrugated construction) static wire placed between the tube and cover. Clear, high-density Pliovic® helix reinforcement.

Temperature: -15°F to 158°F

Sizes: 1 1/2" - 3"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Alum. Cam and Groove			
		50 ft Assy	Price	100 ft Assy	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1	250	NTX100-50		NTX100-100		NTX100-10CE		NTX100-20CE	
1-1/2	250	NTX150-50		NTX150-100		NTX150-10CE		NTX150-20CE	
2	250	NTX200-50		NTX200-100		NTX200-10CE		NTX200-20CE	
2-1/2	250	NTX250-50		NTX250-100		NTX250-10CE		NTX250-20CE	
3	250	NTX300-50		NTX300-100		NTX-300-10CE		NTX-300-20CE	

Plicord® Blue Flour Discharge Hose

Construction: 3/16" gauge white Pureten™ tube (FDA compliant). Blue Plioflex™ rubber (wrapped impression) cover. Spiral-plied synthetic fabric with 2 antistatic wires reinforcement.

Temperature: -40°F to 180°F

Sizes: 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Alum. Cam and Groove			
		20 ft	Price	50 ft	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
4	150	PBF400-20		PBF400-50		PBF400-10CE		PBF400-20CE	

Plicord® Brewline® Brewers Hose

Construction: White chlorobutyl rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03) tube. Red Versigard® with a white spiral stripe (wrapped impression) cover. Spiral-plied synthetic fabric, 4 plies to 1 1/2" I.D.; 6 plies over 1 1/2" I.D. reinforcement.

Temperature: -40°F to 220°F

Sizes: 1" - 3"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Alum. Cam and Groove			
		50 ft	Price	100 ft	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
1	250	BRL100-50		BRL100-100		BRL100-10CE		BRL100-20CE	
1½	250	BRL150-50		BRL150-100		BRL150-10CE		BRL150-20CE	
2	250	BRL200-50		BRL200-100		BRL200-10CE		BRL200-20CE	
3	250	BRL300-50		BRL300-100		BRL300-10CE		BRL300-20CE	

Plicord® Extremeflex™ Food Grade Wet Food Hose

Construction: White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03) tube. White or gray Chemivic™ corrugated synthetic rubber (wrapped impression) cover. Spiral-plied synthetic fabric with galvanized wire helix reinforcement.

Temperature: - 25°F to 212°F

Sizes: 2" - 4"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Alum. Cam and Groove			
		20 ft	Price	50 ft	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
2	150	FXG200-20		FXG200-50		FXG200-10CE		FXG200-20CE	
3	150	FXG300-20		FXG300-50		FXG300-10CE		FXG300-20CE	
4	150	FXG400-20		FXG400-50		FXG400-10CE		FXG400-20CE	

White Flexwing® Heavy-Duty Rubber Hose

Construction: White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03) tube. White Chemivic synthetic rubber (wrapped impression) cover. Spiral-plied synthetic fabric with galvanized wire helix reinforcement.

Temperature: - 25°F to 230°F

Sizes: 3/4" - 3"



Hose Inside Dia. (in.)	Max. Pressure (psi)	Bulk Hose				Stainless Cam and Groove			
		20 ft	Price	50 ft	Price	10 ft Assy C + E	Price	20 ft Assy C + E	Price
3/4	150	FTH075-20		FTH075-50		FTH075-10CE		FTH075-20CE	
1	150	FTH100-20		FTH100-50		FTH100-10CE		FTH100-20CE	
1-1/4	150	FTH125-20		FTH125-50		FTH125-10CE		FTH125-20CE	
1-1/2		FTH150-20		FTH150-50		FTH150-10CE		FTH150-20CE	
2		FTH200-20		FTH200-50		FTH200-10CE		FTH200-20CE	
3		FTH300-20		FTH300-50		FTH300-10CE		FTH300-20CE	